

CPC-II

Compact Pulse Compressor for Vitara

The CPC-II pulse compressor accessory for Vitara is designed to deliver near transform-limited pulses at the target sample. The CPC-II achieves this by introducing continuously variable negative Group Delay Dispersion (GDD/prechirp) to precisely compensate for normal dispersion of downstream optics. Using chirped-mirror technology, the CPC-II provides an ultra-compact footprint for maximum ease-of-use and the input and output beam ports are in line to enable simple experimental setups.



FEATURES & BENEFITS

- Maximizes peak power for enhanced nonlinear processes
- Coarse and fine GDD control for precise pulse compression
- In-line input and output ports for easy alignment
- Pre-compensates for positive dispersion from downstream optics
- Ultra-compact footprint

APPLICATIONS

- Second Harmonic Generation
- THz Generation
- Coherent Anti-Stokes
 Raman Scattering (CARS)
- · Multiphoton Imaging
- Non-Linear Optics




SPECIFICATIONS ¹	CPC-II
Typical GDD Compensation Range (fs²) (±10%)	-440 to -2640
Course GDD Tuning Step Size (fs ²)	10 steps of approx220
Fine GDD Tuning (fs ²)	Continuous over approx. +400
Transmission Efficiency (%)	>75
Input Wavelength Range (nm)	700 to 900
Input Bandwidth (nm)	≤125
Typical Output Pulse Length ² when used with Vitara-T ³ (fs)	
for 100 nm bandwidth	<15
for 50 nm bandwidth	<25
for 30 nm bandwidth	<40
Input Beam Diameter (mm)	~2


- 1 Subject to change without notice.
- 2 Assumes an autocorrelation deconvolution factor of 0.65.
 3 Pulse length and bandwidth defined at FWHM.

TYPICAL PERFORMANCE DATA





Typical Compressed Pulse Width from Vitara-T with CPC-II (pulse measured using FC Spider)





127.0 mm (5.00 in.)

MECHANICAL SPECIFICATIONS

| Top View | Output | Side View | (1.36 in.) | Front View | Front View | (4.75 in.) | (4.75 in.)



Coherent, Inc., 5100 Patrick Henry Drive Santa Clara, CA 95054 p. (800) 527-3786 | (408) 764-4983 f. (408) 764-4646

tech.sales@coherent.com www.coherent.com

285.8 mm (11.25 in.)