

135W, 976nm, 200µm, Fiber-Coupled, Conduction-Cooled, Tailored Bar Module

Features

- Conduction-cooled diode laser bars inside
- Single wavelength
- High coupling efficiency

Optional Accessories

- Integrated power meter
- Wavelength stabilization
- Back reflection filter
- Integrated NTC temperature sensor



Device Specification

Optical Parameters ¹		Units
Center Wavelength ²	nm	976
Wavelength Tolerance	nm	±2
Output Power ³	W	135
Spectral Width (FWHM)	nm	<5
Slope Efficiency	W/A	>6.0
Fiber Parameters		
Fiber Core Diameter	µm	200
Numerical Aperture	NA	0.22
Fiber Connector		SMAQ
Electrical Parameters ¹		
Power Conversion Efficiency	%	>45
Threshold Current (I_{TH})	A	<3.5
Operating Current (I_{OP})	A	<30
Operating Voltage (U_{OP})	V	<11.5
Thermal Parameters		
Operating Temperature ^{3, 4, 5}	°C	+20 to +25
Storage Temperature ⁵	°C	+5 to +60
Coolant Flow Rate	l/h	150
Water Temperature	°C	+20 to +25
Purity		Tap Water

¹Data at 25°C cold plate temperature, unless otherwise stated.

²Others available upon request.

³Reduced lifetime if used above nominal operating conditions.


⁴Additional information available upon request.

⁵A non-condensing environment is required for storage and operation.

135W, 976nm, 200 μ m, Fiber-Coupled, Conduction-Cooled, Tailored Bar Module

DILAS
The diode laser company.

Package Dimension



All rights reserved. DILAS reserves the right to change products specifications without notice. For handling precautions, please reference the general handling instruction manual.

For complete details, please contact your local DILAS sales representative or visit our website at www.DILAS.com.

Europe
DILAS Diodenlaser GmbH
Galileo-Galilei-Straße 10
55129 Mainz
Germany
Phone: +49 (0)6131 9226 0
Fax: +49 (0)6131 9226 257
Email: sales@DILAS.de

North America
DILAS Diode Laser, Inc.
9070 South Rita Road
Suite 1500
Tucson, AZ 85747
Phone: +1 (520) 232-3480
Fax: +1 (520) 232-3499
Email: sales@DILAS-INC.com

China & Taiwan
DILAS Diodenlaser GmbH
China Sales Office
Room 206, Sunplus Technology, Bldg. 2
No. 1077 Zu Chongzhi Road
Hi-Tech Park, Shanghai 201203,
P.R. China
Phone: +86 (0) 21-6855-2216
Fax: +86 (0) 21-5027-3793
Email: sales@DILAS-CHINA.com.cn