

Features

- Very low smile
- Available with fast-axis collimation
- Different heatsink geometries available



Device Specification

Optical Parameters ¹	Units	CW	QCW ⁷
Center Wavelength Range ³	nm	1470	1470
Center Wavelength Tolerance	nm	±20	±20
Output Power ² (P _{OP})	W	20	80
Number of Emitters	#	20	20
Emitter Size	µm	100	100
Fill Factor	%	20	20
Spectral Width (FWHM)	nm	<12	<14
Slope Efficiency	W/A	>0.46	>0.50
Fast-Axis Divergence ⁵ (90%)	degree	<60 ⁶	<60 ⁶
Slow-Axis Divergence (90%)	degree	<8 ⁶	<8 ⁶
Wavelength Temp. Coefficient	nm/°C	~0.58	~0.58

Electrical Parameters ¹			
Power Conversion Efficiency	%	>28	>24
Threshold Current (I _{TH})	A	<11	<13
Operating Current (I _{OP})	A	<60	<160
Operating Voltage (V _{OP})	V	<1.40	<2.00

Thermal Parameters ¹			
Operating Temperature Range ⁴	°C	+20 to +30	+20 to +30
Storage Temperature Range ⁴	°C	0 to +55	0 to +55
Recommended Heatsink Capacity Per Bar	W	>80	>20

¹Data at 25°C cold plate temperature, unless otherwise stated.

²Reduced lifetime if used above nominal operating conditions.

³Others available upon request.


⁴A non-condensing environment is required for storage and operation below the ambient dew point.

⁵For fast-axis collimation using FAC lens: divergence <8mrad.

⁶Bar manufacturer information.

⁷Depending on pulse width and duty cycle.

Package Dimension



Heatsink for MY Diode Laser Bars with Fast-Axis Collimation Lens:

Beam heights available:


M3 mount = 7.7mm

M10 mount = 7.95mm

M8 mount = 8.0mm

Upon request:

M7 mount = 6.0mm



©2017 DILAS. All rights reserved. DILAS reserves the right to change product specifications without notice. For handling precautions, please reference the general handling instruction manual.

For complete details, please contact your local DILAS sales representative or visit our website at www.DILAS.com.

Europe
DILAS Diodenlaser GmbH
 Galileo-Galilei-Straße 10
 55129 Mainz
 Germany
 Phone: +49 (0)6131 9226 0
 Fax: +49 (0)6131 9226 257
 Email: sales@DILAS.de

North America
DILAS Diode Laser, Inc.
 9070 South Rita Road
 Suite 1500
 Tucson, AZ 85747
 Phone: +1 (520) 232-3480
 Fax: +1 (520) 232-3499
 Email: sales@DILAS-INC.com

China & Taiwan
DILAS Diodenlaser GmbH
 China Sales Office
 Room 206, Sunplus Technology, Bldg. 2
 No. 1077 Zu Chongzhi Road
 Hi-Tech Park, Shanghai 201203,
 P.R. China
 Phone: +86 (0) 21-6855-2216
 Fax: +86 (0) 21-5027-3793
 Email: sales@dilas-china.com.cn