

600 Micron Core Power Delivery Fiber

Coherent | Coherent's specialty multimode step-index fibers are designed for compatibility with the majority of fibercoupled, bar and stack diode-laser packages and support the diode laser power delivery market. This fiber features a 600 micron core diameter witha 0.22 NA and a 660 micron clad diameter with Coherent | Coherent's proprietary NuCoat-FA, a low refractive index fluoroacryalte coating, for added power confinement. Other fiber diameters are available upon request.

Typical Applications

- Fiber coupled diode lasers
- · Couplers and pump combiners

Features & Benefits

- 0.22 NA Compatible with the majority of fiber-coupled, diode-laser packages
- Exceptional geometric uniformity and core/clad concentricity Ease of coupling to pump diodes
- Pure silica core High resistance to optical damage
- Clean room fiber draw Eliminates coating "hot spots"
- All fiber proof tested to > 100 kpsi Critical for ensuring long term reliability when coiling

Optical Specifications

MM-S600/660-22FA 1362303

700 - 2200 nm

 0.220 ± 0.020

≥ 0.46

Low

Operating Wavelength Core NA First Cladding NA (5%) OH Level

Geometrical & Mechanical Specifications

Cladding Diameter 6 Core Diameter 6 Coating Diameter 8 Core/Clad Offset 2 Coating Material L Short Term Bend Radius 2 Long Term Bend Radius 2 Prooftest Level 2

660.0 ± 12.0 μm 600.0 ± 12.0 μm 875.0 ± 30.0 μm ≤ 7.00 μm Low Index Acrylate ≥ 34 mm ≥ 100 mm ≥ 100 kpsi (0.7 GN/m²)



Nufern • 7 Airport Park Road, East Granby, CT 06026 • 860.408.5000 • Toll-free 866.466.0214 • Fax 860.844.0210 • Email: tech.sales@coherent.com www.coherent.com ; www.shop.coherent.com • Coherent products are manufactured under an ISO 9001:2008 certified quality management system.



Custom developed fiber (FUD) specifications are subject to change without notice. Other configurations such as alternative form factors, optimized cut-off and UV cured color coating may be available. Let us know how Coherent can assist with your requirements.